

Industrial fluids



Relton

Rapid Tap from Relton is the best. Laboratory tests measuring the amount of torque required to tap 1/4-20 holes in both mild and stainless steels were conducted. Rapid Tap required less average torque than any other brand tested. It's more than your best bet... it's a sure thing!

1 Non-flammable, non-toxic & ozone friendly

Does NOT contain 1,1,1 Trichloroethane or other ozone-depleting substance.

2 Improves surface finish, machining accuracy and tool life

Leaves a fine machined finish even on tough materials such as aluminum, beryllium, brass, bronze, cast iron, copper, inconel, magnesium, molybdenum, stainless steel and stellite.

3 Versatile



Relton Rapid Tap® cutting fluid

	Unit/Container	Approx. Weight
RT114	24 x 4 oz/118 ml	11.00 lbs/case
RT455	12 x 16 oz/455 ml	17.00 lbs/case
RT4	4 x 1 US gal/3.785L	42.00 lbs/case

Relton OPTION 1® cutting fluid

An environmentally friendly cutting fluid that has no chlorine, no sulfur, a non-toxic formula that's safe to use. Water based.



	Unit/Container	Approx. Weight
OPT455	12 x 16 oz/473 ml	14.80 lbs/case
OPT4	4 x 1 US gal/3.785L	36.10 lbs/case

Relton A-9® aluminum cutting fluid

Use for tapping, drilling, boring, milling, sawing, reaming and broaching. Specifically designed for aluminum; also works well on many other metals.



	Unit/Container	Approx. Weight
A9114	24 x 4 oz/118 ml	9.00 lbs/case
A9455	12 x 16 oz/473 ml	16.00 lbs/case
A94	4 x 1 US gal/3.785L	33.00 lbs/case

